

## NYACOL® NYAGRAPH 35 Expandable Graphite Flame Retardant

Nyacol NYAGRAPH 35 is an intumescent flame retardant that offers the following advantages:

- Halogen-free
- Low smoke
- Non-dripping
- Reduced heat release
- Lower in toxic gases
- Insulating

NYAGRAPH 35 is a natural material based on processed graphite ore.

The ore is treated with sulfuric acid in what is called an intercalation process.

The material is washed and neutralized to prevent corrosion of metal parts when processed by the user.

Excessive shear should be avoided.

NYAGRAPH 35 may be used in polyurethanes, sealants, bitumens, rubbers, adhesives, coatings, and polymers.


NYAGRAPH 35 may also be used in conjunction with other flame retardants to provide improved flame-retardant and smoke-suppressant properties to a material.

### TYPICAL PROPERTIES

Particle Size, % 100 mesh:	Min. 80
Appearance:	Soft black particles
pH:	6 – 8
Onset Temperature, °C:	180 – 200
Expansion Volume, cm <sup>3</sup> /g:	≥ 35
Moisture, %:	0.2 – 1.0
Purity, %:	≥ 95.0
Specific Gravity, g/cm <sup>3</sup> :	1.9 – 2.1
Bulk Density, g/cm <sup>3</sup> :	0.45 – 0.6
Free Acid, mg/g NaOH:	Max. 0.5

### TYPICAL PARTICLE SIZE DISTRIBUTION, %

Over 300µm	0
300µm – 180µm	1 – 5
180µm – 150µm	9 – 15
150µm – 75µm	35 – 50
75µm – 45µm	20 – 25
< 45µm	15 – 25



### FOR ADDITIONAL INFORMATION OR TO PLACE AN ORDER

Nyacol Nano Technologies, Inc.  
Megunko Road ~ P.O. Box 349  
Ashland, MA 01721-0349 U.S.A.

Telephone: 508-881-2220 Local Area  
800-438-7657 Toll-Free  
Fax: 508-881-1855

Information herein is accurate to the best of our knowledge. Suggestions are made without warranty or guarantee of results. Before using, user should determine the suitability of the product for the intended use and user assumes risk and liability in connection therewith. We do not suggest violation of any existing patents or give permission to practice any patented invention without a license. 080110